

## PRODUCT DATA SHEET

# **ENEOS RACING PRO 10W-50**

## **DESCRIPTION**

**ENEOS RACING** *PRO* motor oil line was developed for the most extreme racing conditions. It has been formulated to provide relentless performance for serious professionals.

**ENEOS RACING** *PRO* **10W-50** uses a combination of Ester and low viscosity fully synthetic base oil that provides extra-high horsepower, ensuring ultimate performance for properties including anti-wear, low oil consumption, exceptional oxidation stability, engine component cleanliness, and outstanding rust and corrosion protections.

#### **APPLICATION**

Suggested uses of **ENEOS RACING** *PRO* **10W-50** include teams and drivers competing in GT racing, drift, sprint, stock car, rally, formula racers, and drag racing.

### TYPICAL PROPERTIES

| Test                        |         | Method | ENEOS RACING<br>PRO 10W-50 |
|-----------------------------|---------|--------|----------------------------|
| Appearance                  |         | Visual | Clear                      |
| Density (15°C) g/cm3        |         | D4052  | 0.909                      |
| Flash point (COC) °C        |         | D92    | 230                        |
| Kinematic viscosity         |         |        |                            |
| (40°C) mm2/s                |         | D445   | 104.2                      |
| (100°C) mm2/s               |         | D445   | 18.1                       |
| HTHS (150°C) mPa-s          |         | D4683  | 4.5                        |
| Viscosity index             |         | D2270  | 193                        |
| CCS viscosity (-25°C) mPa-s |         | D5293  | 5,400                      |
| Pour point °C               |         | D5950  | -48                        |
| TAN mgKOH/g                 |         | D664   | 2.8                        |
| TBN (HCIO4 method) mgKOH/g  |         | D2896  | 8.3                        |
| Foaming prevention, ml/ml   | Seq. II | D892   | 10/0                       |
| NOACK 250°C, 1Hr            |         | D5800  | 8.9                        |
| Element Analysis mass%      | Р       | D4951  | 0.11                       |
|                             | Zn      | D4951  | 0.12                       |
|                             | Мо      | D4951  | 0.05                       |

Revised 04/18

**ENEOS** is the corporate brand name of JX Nippon Oil & Energy Corporation, the largest oil company in Japan. ENEOS brand motor oil is developed to exceed the highest standards of the automotive industry. ENEOS product ranges from motor oil that offers optimal performance protection under the most extreme temperature variations, to ecologically friendly motor oil that provides superior fuel saving capacity. For more information please visit www.eneos.us.