



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

Print date: 2019-03-19

1. Product identifier:

Engine oil
FANFARO 6719 5W-30, Volume: 5 l

2. Product manufacturing date:

2019-03-12

Batch №

G-2138

Expiry date

03.2024

3. Handling and storage:

Store in a dry, cool place with sufficient ventilation. Keep out of direct sunlight. Storage room do not smoke. Keep out of children. For more information see the safety data sheet.

4. Product quality parameters:

FANFARO 6719 5W-30			
Product specification	SAE 5W-30 API SN ACEA C3 MB 229.51 VW 504.00/507.00 VW TL 52195 BMW LL-04; Porsche C30		
Parameter name	Standard	Results	Test method
Viscosity at 100°C, cSt	11-12.5	12,39	ASTM D-445
Viscosity at 40°C, cSt	-	72,90	ASTM D-445
Viscosity index, min	165	169	ASTM D-2270
Dynamic viscosity [cP], at -30°C, max	6600	5503	ASTM D 5293
Total base no. mgKOH/g, min	7,0	8,37	ASTM D-2896
Flash point, open cup, °C	220	224	ASTM D-92
Pour point, °C, max	-35	-42	ASTM D-97
Density at 15°C, kg/l, max	0,9	0.85	ASTM D-1298
High-shear-rate viscosity, cP at 150°C, min	3,5	3,56	ASTM D-4741

Responsible for analysis: Daiva Burbaitė

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL. (8 46) 34 03 45, FAKS (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT