

Technical Information

Transmission Oil Recommendation



ZF-LifeguardFluid -Maximal Performance for **7F Automatic Transmissions**

The ZF-LifeguardFluid* products make up a range of synthetic heavy-duty oils intended exclusively for ZF's automatic car transmissions. ZF-LifeguardFluid oils were developped specifically for ZF's automatic 5-speed, 6-speed, and 8-speed transmissions.

Subjected to extreme testing, ZF-LifeguardFluid guarantees maximum performance of the automatic transmission. At the same time, the wear of heavily loaded components is minimized owing to the specifically matched oils. And a long service life is achieved.

ZF-LifeguardFluid is a firm element of production as well as remanufactured transmissions and must therefore be used in cases of repair.

Oil regeneration and oil-filter change beyond 100.000 km will have a positive effect on the service life and value of a thermally heavily loaded automatic transmission; and the original shifting comfort will be restored. Use of other oils as a rule results in early transmission





LifeGuardFluid 5 S671 090 170 1 - liter bottle S671 090 172 20 - liter can

LifeGuardFluid6 S671 090 255 1 - liter bottle S671 090 253 20 - liter can

LifeGuardFluid8 S671 090 312 1- liter bottle S671 090 311 20 - liter can S671 090 171 210 - liter barrel S671 090 252 210 - liter barrel S671 090 310 210 - liter barrel

- Specifically matched transmission fliuds for exclusive use in ZF automatic transmission.
- Less material wear and softer shifting operations due to constant friction behavior.
- Less vibration due to the controlled slip of the converter lockup clutch.
- Maximum sound dampening due to low viscosity.
- Improved lubricating film stability in all performance and temperature ranges.
- Improved economy thanks to maximum reduction of fuel consumption, which also reduces emissions

ZF Services North America LLC 777 Hickory Hill Drive Vernon Hills IL, 60061/USA

© 7F Automotive Services NA

Printed in USA Rev 1.0

E-Mail: sl-support@ZF.com

9/29/10



Technical Information

Transmission Oil Recommendation





CAUTION!

- ZF transmissions have been engineered to operate only with ZF approved fluids. Other fluids have not been tested. These fluids may cause internal damage or unpredictable results when used with ZF overlapping shift technology or mechatronic assemblies.
- Transmission fluids are not all alike and are not interchangeable. Each ZF transmission requires a specific ZF fluid to operate properly. The use of incorrect fluid may cause damage to internal parts. Be certain the correct fluid is used.
- The use of any fluid additives is prohibited as the result will unpredictably change fluid properties potentially resulting in transmission failure.

ZF 6 Speed fluid reference

Application	Make	Fluid Type	
Application 6HP19 6HP19X (except for Audi Q7) 6HP26 6HP26A61* (excluding vehicles with Audi W12 engine 6HP26X 6HP32 6HP32A*	Make BMW Jaguar Audi Land Rover Bentley	Fluid Type LifeGuardFluid6	ZE-LIFE GUARD FLUID

Application	Make	Fluid Type	
6HP26A61 *			
(Only for		LifeGuardFluid8	
vehicles with			
Audi W12 engine	Audi		
6HP19A *			
6HP19X (Only			ZF-LIFEGUARD
for Audi Q7)			FLUID
			indipentation into Proceedings (Internal Internal

ZF Services North America LLC

© ZF Automotive Services NA

Printed in USA

Rev 1.0

9/29/10

777 Hickory Hill Drive Vernon Hills IL, 60061/USA

E-Mail: sl-support@ZF.com



Technical Information



Transmission Oil Recommendation

ZF 5 Speed fluid referance



Type plate examples see above for correct transmission - type plate color - fluid type

4 Speed fluid referance

Application	Make	Type plate color	Fluid Type	BMW MINI CVT
4HP14	All	Black	Dexron III	Used MINI CVT applications
4HP18				ZF number on type plate
4HP18E				481978
4HP18FLA				ESSO EZL 799
4HP18FLE				481 336 5 liter bottle
4HP22				5 liters required for 1 fluid
4HP22A				service.
4HP22HL				
4HP24				
4HP24A				
4HP20	All	Green	LifeGuardFluid 5	5

ZF Services North America LLC

777 Hickory Hill Drive Vernon Hills IL, 60061/USA

© ZF Automotive Services NA

Printed in USA

Rev 1.0

E-Mail: sl-support@ZF.com

9/29/10