

Synthetic oil.

Developed specially to meet the requirements of the latest generation Ford Petrol engines which require the use of a lubricant with grade SAE 5W-20 viscosity with the FORD WSS-M2C948-B specification.

Designed for EcoBoost and Duratec engines (except the Ford Ka, Focus ST and Focus RS).

PROFIVE F948 is used to improve "Fuel Economy" by 0.9%.

Its low viscosity in cold conditions protects the engine from start up.

PERFORMANCES

Standards: ACEA A1/B1
API SN

Specifications:
FORD WSS-M2C948-B*

* Approval under progress

ORGANISATIONS & MANUFACTURERS - Scope of application -

ACEA A1/B1: For Fuel Economy Petrol and Diesel engines.

API SN: Petrol =SM+ exhaust system protection + Turbocompressor.

FORD WSS-M2C948-B: Specification for European Petrol vehicles, mainly for the new EcoBoost engines, but also compatible with Sigma and I4 Duratec engines (5W/20 factory fill and service fill).

Characteristics	Standards	Units	Values
Viscosity 40°C	ASTM D445	mm ² /s	42.4
Viscosity 100°C	ASTM D445	mm ² /s	7.9
Viscosity index	NFT 60-136	-	161
Pour point	ASTM D2602	°C	-36
Flash point	ASTM D92	°C	200
Density at 20°C	NFT 60-101	g/cm ³	0.850

Characteristics are given for information only and correspond with our manufacturing standards. IGOL reserves the right to modify them to provide its customers with the benefits of technical progress. Before using this product read the instructions for use and the environmental impacts mentioned in the technical and safety data sheets. The information given above is based on the current level of knowledge relative to the product concerned. The product user should take all useful precautions relative to its use. IGOL can in no circumstances be held responsible for damage resulting from incorrect use.

Documentary reference : I-119-1507

Date of issue : 16/01/2018

