



Product Data

BP Visco 5000 M 5W-30

Cleanguard Engine Protection Technology

Description

BP Visco with Cleanguard Engine Protection Technology keeps your engine cleaner for longer.

Your car runs better if the engine is kept clean.

Cleanguard technology keeps your engine clean by preventing dirt such as carbon and sludge from sticking to sensitive engine parts and the vital oil ways.

Cleanguard technology slows down the formation of carbon and sludge and wraps up dirt so that they cannot stick to the engine.

Application

BP Visco 5000 M 5W-30 with Cleanguard Engine Protection Technology is a premium quality synthetic engine oil suitable for use in automotive gasoline and diesel engines where the manufacturer recommends ACEA C3, API SN/CF or earlier specification 5W-30 lubricant. Visco 5000 M 5W-30 is also approved for use by leading vehicle manufacturers, please refer to the specifications section and your owner's handbook.

*GM dexos2®: supersedes GM-LL-B-025 and GM-LL-A-025 : GB2C1124082.

Advantages

BP Visco 5000 M 5W-30 is a premium quality synthetic engine oil that provides:

- Superior engine cleanliness
- Comprehensive engine protection
- Prolongs the life of modern emissions systems
- Reduced harmful emissions

Typical Characteristics

Name	Method	Units	BP Visco 5000 M 5W-30
Density @ 15°C, Relative	ASTM D4052	g/ml	0.852
Viscosity, Kinematic 100°C	ASTM D445	mm²/s	12.5
Viscosity, CCS -30°C (5W)	ASTM D5293	mPa.s (cP)	6500
Viscosity, Kinematic 40°C	ASTM D445	mm²/s	75
Viscosity Index	ASTM D2270	None	165
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	0.846

Product Performance Claims

ACEA C3
API SN/CF
BMW Longlife-04
dexos2®*
MB-Approval 229.31/ 229.51

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 5000 M 5W-30
22 Oct 2015
BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353
www.bp.com/uk