



Typical Inspection Data:

Density @ 20°C	0.865 g/cm ³
Viscosity @ 100°C	13.9 cSt
Viscosity @ 40°C	93 cSt
Viscosity Index	153
Viscosity CCS @ -25°C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	1.3%
Zinc	0.11%
Calcium	0.24%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

X-Flow Type XS 10W-40 Semi Synthetic

Recommended by Comma for applications requiring:

ACEA A3/B3
API SL/CF

Direction of use:

- Semi synthetic 10W-40 oil suitable for petrol and diesel vehicles including those with fuel injected, multivalved and turbo charged engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 03.05.2019