



A brand of **TOTAL**

# EVOLUTION 900 FTA 5W-40



*Top performance motor oil using ELF fully synthetic technology, intended for lubricating gasoline passenger car engines*

## APPLICATIONS

### Most recent technology engines

- Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies

### Even in very severe conditions

- Suitable for all types of service (urban, highway or motorway) especially in very severe conditions

### Vigorous driving, all times of year

- Meets needs of the motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

## PERFORMANCES

### International Specifications

- API SN/CF

## CUSTOMER BENEFIT

### Excellent engine protection

- Ensures outstanding engine life, keeps engine clean with excellent dispersant and detergent properties

### Optimal performance

- Extended oil change intervals

### Cold starts

- Facilitates ignition in very cold weather and maintains protection of parts even at high temperature

## CHARACTERISTICS

EVOLUTION 900 FTA 5W-40	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	855
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14
Viscosity index	ASTM D2270	-	166
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	243

The typical characteristics mentioned represent mean values