



A brand of **TOTAL**

## EVOLUTION 900 SXR 5W-40



**Very high performance lubricant based upon ELF synthetics technology, designed for lubricating all Diesel car engines.**

### APPLICATIONS

**All Diesel engines, especially those of recent technology**

- Recommended for all supercharged or naturally aspirated Diesels in cars and light vans.

**Even in very severe conditions**

- Suitable for all types of service (urban, or on the highway or motorway) especially in very severe conditions.

**Fast driving**

- For all types of driving, especially at high speed.

**All times of year, even the coldest weather**

- Specially designed to meet the demands of the motor manufacturers as regards extended oil-change.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

### PERFORMANCES

**International specifications**

ACEA A3/B4  
API: SN/CF

**OEMs approvals**

RENAULT RN0710 et RN0700

### CUSTOMER BENEFITS

**Best possible performance**

- Excellent engine protection, particularly against wear in the timing system.

**Excellent engine cleanliness and protection**

- Ensures an exceptionally clean engine.

**Easier starting in very cold conditions**

- Outstanding thermal stability and oxidation resistance, guaranteeing that the oil will not degrade even in conditions of very severe use.

**Longer engine life**

- Immediate lubrication of engine components during cold starts, leading to longer engine life.

**Extended oil-change intervals**

- Lubricant performance sustained over time for extended oil change intervals.

### CHARACTERISTICS

	Method	Units	SAE Grade 5W-40
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	855
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	14,7
Viscosity index	ASTM D2270	-	172
Pour point	ASTM D97	°C	- 42
Flash point	ASTM D92	°C	230
B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values