



A brand of **TOTAL**

## EVOLUTION 900 FT 5W-30



**Very high performance lubricant using ELF synthetic technology, intended for lubricating all Gasoline and Diesel car engines.**

### APPLICATIONS

**All Gasoline and Diesel engines, particularly those of recent technology**

- Recommended for all recent engines (multivalve, turbocharged, with or without catalytic converter), supercharged or not, in cars and light vans.

**The most severe journeys**

- Suitable for all journeys (in town, on highways or motorways) and particularly in severe conditions.

**« Vigorous » driving, all times of year**

- For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

### PERFORMANCES

**International specifications**

ACEA : A3/B4  
API: SL/CF

**OEMs approvals**

VOLKSVAGEN VW 502.00 / 505.00  
MERCEDES BENZ MB-Approval 229.5 (backward compatible MB-Approval 229.3)

### CUSTOMER BENEFITS

**Extended oil change intervals**

- Meets the most demanding OEMs requirements in terms of oil change intervals, thanks to an outstanding oxidation resistance.

**Excellent engine protection against wear**

- Gives the engine an excellent wear protection, thanks to its very solid additive package.

**High engine cleanliness**

- Ensures maximum engine cleanliness.

### CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	851
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	67,5
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	11,7
Viscosity index	ASTM D2270	-	170
Pour point	ASTM D97	°C	- 39
Flash point	ASTM D92	°C	230
B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values