



A brand of **TOTAL**

EVOLUTION 900 SXR 5W-30



Very high performance lubricant using ELF synthetics technology, « Fuel Economy », intended for all Gasoline and Diesel car engines.



APPLICATIONS

All Gasoline and Diesel engines

- Recommended for all Gasoline engines (multivalve, turbocharged, with or without catalytic converter) and all Diesel engines – with or without turbocharging – in cars and light vans.

Direct Injection

- Particularly recommended to meet the enhanced requirements of direct injection Diesel engines.

The most severe journeys All times of year “Vigorous” driving

- Suitable for all journeys (in town, on highways and motorways) and particularly in severe conditions.
- For all driving styles, particularly “vigorous” and high speeds.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications

ACEA : A5/B5
API: SL/CF

OEMs approvals

RENAULT RN0700
(except 2.0 16V Renault Sport, 2.0 T Renault Sport, V6 Renault Sport)

CUSTOMER BENEFITS

Fuel saving

- Saves fuel.

Very advanced Performance

- Outstanding engine protection particularly against wear.

Extension of engine's lifetime

- Outstanding thermal stability and oxidation resistance, preventing any degradation even in very severe conditions.

Extension of out charge intervals

- Elf Evolution 900 SXR 5W30 has been engineered in order to comply with car manufacturers requirements in terms of extended oil change intervals.

CHARACTERISTICS

	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	kg/m ³	857
Viscosity at 40°C	ASTM D445	mm ² /s	55,6
Viscosity at 100°C	ASTM 445	mm ² /s	9,9
Viscosity index	ASTM D2270	-	170
Pour point	ASTM D97	°C	- 36
Flash point	ASTM D92	°C	230
T.B.N.	ASTM D2896	mgKOH/g	10

The typical characteristics mentioned represent mean values