



A brand of **TOTAL**

ELF EVOLUTION 900 SM 5W-40 & 5W-50



*Top performance motor oil using ELF fully synthetic technology,
intended for lubricating gasoline passenger car engines*

APPLICATIONS

Most recent technology engines

- Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies

Even in very severe conditions

- Suitable for all types of service (urban, highway or motorway) especially in very severe conditions

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SM/CF

CUSTOMER BENEFITS

Excellent engine protection

- ☐ Excellent start-up performance, prevents sludge build-up and controls oxidation

Optimal performance

- ☐ Optimum power and performance under most severe driving conditions

Low emission vehicles

- ☐ Fully compatible with all gasoline emission control devices

CHARACTERISTICS

	Method	Units	SAE Grade 5W-40	SAE Grade 5W-50
Density at 15°C	ASTM D1298	Kg/m ³	852	855
Viscosity at 40°C	ASTM D445	mm ² /s	91.1	130
Viscosity at 100°C	ASTM 445	mm ² /s	14.7	19.6
Viscosity index	ASTM D2270	-	169	173
Pour point	ASTM D97	°C	-36	-36
Flash point	ASTM D92	°C	230	245

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 900 SM 5W-40 & 5W-50

Last update of this datasheet: 05/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.