



A brand of **TOTAL**

EVOLUTION 900 FTX 5W-30



Top performance motor oil using ELF fully synthetic technology, intended for lubricating gasoline passenger car engines



APPLICATIONS

- Most recent technology engines**
 - Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies
- Even in very severe conditions**
 - Suitable for all types of service (urban, highway or motorway) especially in very severe conditions
- Vigorous driving, all times of year**
 - Meets needs of the motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

- International Specifications**
 - API SN/CF; ILSAC GF-5

CUSTOMER BENEFIT

- Fuel Economy**
 - Promoted fuel saving
- Excellent engine protection**
 - Excellent start-up performance, prevents sludge build-up and controls oxidation
- Optimal performance**
 - Optimum power and performance under most severe driving conditions
- Low emission vehicles**
 - Fully compatible with all gasoline emission control devices

CHARACTERISTICS

EVOLUTION 900 FTX 5W-30	Method	Units	SAE Grade 5W-30
Density at 15°C	ASTM D1298	Kg/m ³	850
Viscosity at 40°C	ASTM D445	mm ² /s	57
Viscosity at 100°C	ASTM 445	mm ² /s	10
Viscosity index	ASTM D2270	-	160
Pour point	ASTM D97	°C	-36
Flash point	ASTM D92	°C	235

The typical characteristics mentioned represent mean values