



A brand of **TOTAL**

# ELF EVOLUTION 900 FTX 0W-20 & 5W-20



*Top performance motor oil using ELF fully synthetic technology,  
intended for lubricating gasoline passenger car engines*



## APPLICATIONS

- Most recent technology engines**
  - Recommended for all high performance gasoline engine cars equipped with direct or indirect injection, multi-valve and turbo-charge technologies
- Vigorous driving, all times of year**
  - Meets needs of the motor manufacturers regarding extended oil change intervals
- Even in very severe conditions**
  - Suitable for all types of service (urban, highway or motorway) especially in very severe conditions

Refer to the maintenance book of your vehicle to know the recommendation of the

## PERFORMANCES

**International specifications**      API SN/CF; ILSAC GF-5

## CUSTOMER BENEFITS

- Fuel Economy**       Promoted fuel saving
- Excellent engine protection**       Excellent start-up performance, prevents sludge build-up and controls oxidation
- Optimal performance**       Optimum power and performance under most severe driving conditions
- Low emission vehicles**       Fully compatible with all gasoline emission control devices

## CHARACTERISTICS

	Method	Units	SAE Grade 0W-20	SAE Grade 5W-20
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	848	849
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	43	50
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	8.1	8.7
Viscosity index	ASTM D2270	-	166	153
Pour point	ASTM D97	°C	-39	-36
Flash point	ASTM D92	°C	229	229

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**ELF EVOLUTION 900 FTX 0W-20 &  
5W-20**

Last update of this datasheet: 05/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.