



A brand of **TOTAL**

## ELF EVOLUTION 400 FT

5W-30 ; 10W-30 ; 15W-50; 20W-50



Premium mineral oils designed for petrol and diesel engine oil.  
Suitable for use under standard conditions.

### APPLICATIONS

**Old gasoline and diesel car engines**

• These oils can be used with petrol or diesel engine technologies without particulate filters and engines built prior to 2004 and designed for use with mineral oils in these viscosities.

**In all conditions**

• Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

### PERFORMANCES

**International specifications**

API SM/CF

### CUSTOMER BENEFITS

- Protection and reliability
- Protects engines against deposits.
- Oil film able to withstand high operating temperatures
- Standard drain interval.

### CHARACTERISTICS

	Method	Units	SAE Grade xx-xx
Density at 15°C	ASTM D1298	Kg/m <sup>3</sup>	
Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	
Viscosity at 100°C	ASTM 445	mm <sup>2</sup> /s	
Viscosity index	ASTM D2270	-	
Pour point	ASTM D97	°C	
Flash point	ASTM D92	°C	
B.N.	ASTM D2896	mgKOH/g	

The typical characteristics mentioned represent mean values

**TOTAL LUBRIFIANTS – Immeuble Spazio**  
562, avenue du Parc de l'île  
92029 Nanterre cedex  
France

**ELF EVOLUTION 400 FT**  
Last update of this datasheet: 05/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.  
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.