



A brand of **TOTAL**

ELF EVOLUTION 300 FT

5W-30 ; 10W-30 ; 15W-40; 20W-50



Multi-grade oils designed for old gasoline and diesel passenger car engines.
Suitable for use under standard conditions.

APPLICATIONS

Old gasoline and diesel car engines

•

In all conditions

- Suitable for all conditions (in town, on highways or motorways); Meets needs of motor manufacturers regarding extended oil change intervals

Refer to the maintenance book of your vehicle to know the recommendation of the

PERFORMANCES

International specifications

API SJ/CF

CUSTOMER BENEFITS

- Protection of your engine
- Formulations are designed to resist to oxidation effects between oil changes
- Well-suited for old-generation vehicles and engines.
- Standard drain interval.

CHARACTERISTICS

	Method	Units	SAE Grade xx-xx
Density at 15°C	ASTM D1298	Kg/m ³	
Viscosity at 40°C	ASTM D445	mm ² /s	
Viscosity at 100°C	ASTM 445	mm ² /s	
Viscosity index	ASTM D2270	-	
Pour point	ASTM D97	°C	
Flash point	ASTM D92	°C	
B.N.	ASTM D2896	mgKOH/g	

The typical characteristics mentioned represent mean values

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

ELF EVOLUTION 300 FT

Mise à jour de cette fiche technique : 05/2014



This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard.
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.