



**Product Data Sheet**

**MOTOR OIL RN 5W-30**

**Product Description:**

**MOTOR OIL RN 5W-30** is a high performance fuel saving LOW SAPS oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans specially designed for the latest generation Renault and Nissan diesel engines equipped with a Diesel Particulate Filter (DPF) and all other engines where an ACEA C4 product is required.

**MOTOR OIL RN 5W-30** is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extend oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

**MOTOR OIL RN 5W-30** meets the following performance criteria:

ACEA C4-16                      Renault RN0720                      MB 226.51

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	848
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	66.9
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	12.0
Viscosity Index		ASTM D2270	178
Viscosity CCS @-30°C, max	cP	ASTM D5293	<6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	≤0.5

Product Nr: 4233      Date Issued: 19-02-2019      Date Superseded: 16-01-2018      Revision nr: 04