

Product Data Sheet

ENGINE OIL SHPD 10W-40

Product Description:

ENGINE OIL SHPD 10W-40 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particulate Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

ENGINE OIL SHPD 10W-40 is formulated with high refined synthetic base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.

ENGINE OIL SHPD 10W-40 meets the following performance criteria:

API CK-4
DFS 93K222
CAT ECF-3
JASO DH-2

ACEA E7/E9 DQC III-10-LA MTU Type 2.1

Cummins CES 20086 MAN M3575 Volvo VDS 4.5

Properties		Unit	Test Method	Typical Value
0.15.0				1014/ 10
SAE Grade			SAE J300	10W-40
Density@15°C		kg/m ³	ASTM D4052	864
Kin. Viscosity @40°C		mm²/s	ASTM D7042	97.1
Kin. Viscosity @100°C		mm²/s	ASTM D7042	15.1
Viscosity Index			ASTM D2270	164
Viscosity CCS @-25°C, max	(сР	ASTM D5293	7000
Flash Point COC		°C	ASTM D92	>201
Pour Point		°C	ASTM D7346	-39
Total Base Number		mgKOH/g	ASTM D2896	9.8
Sulpated Ash		%Wt	ASTM D874	1.00
Product Nr: 4246 Date	lssued: 27-03-2018	Date Superseded: 24-01-2018		Revision nr: 04

MB 228.31

Mack EOS-4.5

Renault RLD-3

77 Lubricants B.V. Van Ewijckskade 1G – 1761 JA Anna Paulowna, The Netherlands <u>www.77lubricants.nl;</u> e-mail: info@77lubricants.nl