



## Product Data Sheet

# AUTOGEAR OIL EP 85W-140

### Product Description:

**AUTOGEAR OIL EP 85W-140** is an universal high performance mineral EP gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-4 is been required.

**AUTOGEAR OIL EP 85W-140** is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and Antiwear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

**AUTOGEAR OIL EP 85W-140** exceeds the following performance criteria:

API GL-4          MIL-L-2105

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	85W-140
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	904
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	404
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	28.9
Low-Temperature Brookfield Viscosity @ -12°	cP	ASTM D2983	< 150000
Viscosity Index		ASTM D2270	99
Flash Point	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-15

Product Nr: 4304

Date Issued: 08-02-2018

Date Superseded: 08-08-2011

Revision nr: 02