



Product Data Sheet

AUTOGEAR OIL LS 90

Product Description:

Autogear Oil LS 90 is an extra high performance extreme pressure type automotive gear lubricant specially developed for use in modern high performance passenger cars, sports utility vehicles, vans and light duty trucks with limited slip differentials.

Autogear Oil LS 90 is based on high quality mineral virgin base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Excellent limited slip performance to reduce chatter and improves traction.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.
- Good frictional properties provide improved fuel economy and smoother shift ability

Autogear Oil LS 90 exceeds the following performance criteria:

API GL-5
MB 235.0

MAN 342 M1
Volvo 97310

ZF TE-ML 05C, 07A, 08, 12C, 16E, 17B, 19B, 21C
VW TL 727
Arvin Meritor

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J306	90
Density@15°C	kg/m ³	ASTM D4052	905
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	167.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	15.8
Viscosity Index		ASTM D2270	96
Flash Point COC	°C	ASTM D92	220
Pour Point	°C	ASTM D97	-15

Product Nr: 4313

Date Issued: 24-01-2018

Date Superseded: 08-08-2011

Revision nr: 02