



Product Data Sheet

AUTOGEAR OIL MTF 75W-80

Product Description:

AUTOGEAR OIL MTF 75W-80 is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions, transaxles and (dry-clutch) dual clutch transmissions of various manufacturers. Not suitable for differentials and other API: GL-5 applications

AUTOGEAR OIL MTF 75W-80 is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR OIL MTF 75W-80 exceeds the following performance criteria.:

API: GL-4 Ford WSD-M2C200-C GM 1940764 MTF94 Nissan MT-XZ VW G 009 317 VW G 052 726 VW G 070 726	BMW MTF LT-2 Ford WSS-M2C200-D2 GM 1940768 Honda MTF Nissan MT-XZ TL VW G 052 171 VW G 060 726 VW G50	BMW MTF LT-3 GM 1940004 GM 1940182 Honda MTF II Volvo 97308 VW G 052 178 VW G 052 527 PSA B71 2230	BMW MTF LT-4 GM 19259104 MB 235.10 Honda MTF III Volvo 97309 VW G 052 512 VW G 060 726 Renault (NFJ/NFP/TRJ/TRT/TRZ)
---	--	---	--

Property	Unit	Test Method	Typical Value
SAE Grade		SAE J3000	75W-80
Density@15°C	kg/m ³	ASTM D4052	866
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	51.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.3
Brookfield Viscosity @-40°C	cP	ASTM D2983	<75000
Viscosity Index		ASTM D2270	163
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39

Product Nr: 4338

Date Issued: 21-02-2018

Date Superseded: 31-03-2017

Revision nr: 02