



Product Data Sheet

ATF DX III

Product Description:

ATF DX III is a high quality universal fluid to be used in automatic transmission, torque converters and power steering of passenger car, light vans and commercial vehicles.

ATF DX III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF DX III meets the following performance criteria:

DEXRON IIF/G/H
MAN 339 V1/V2
Mercon

Allison C4
MB 236.10/236.9/236.7/236.5/236.1
ZF 02F/03D/04D

CAT TO-2
Voith 55.6335
ZF 11A/11B/14B/16L

MAN 339 Z1/Z2
Volvo 97341

Properties	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m3	ASTM D4052	864
Kin. Viscosity @40°C	mm2/s	ASTM D7042	41
Kin. Viscosity @100°C	mm2/s	ASTM D7042	7.8
Viscosity Index		ASTM D2270	164
Viscosity Brookfield @-40°, max.	cP	ASTM D2983	< 20000
Flash Point COC	°C	ASTM D92	201

Product Nr: 4322

Date Issued: 21-02-2018

Date Superseded: 17-01-2016

Revision nr: 04