

## Product Data Sheet

## ATF L6S

## **Product Description:**

**ATF L6S** is a high performance full synthetic long life ATF specially designed for all 6-speeds automatic transmissions developed by ZF where a constructor requires a M.1375-4 specification.

**ATF L6S** is based on fully synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High "shear stable".
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

## **ATF L6S** meets the following performance criteria:

M.1375-4 Hyundai SP-IV BMW P/N 83 22 0 142 51	VW G 055 005 Mercon LV 6	Toyota Type WS Dexron VI		Nissan Matic S MB 236.12
Properties		Unit	Test Method	Typical Value
Color			Visual	Colorless to light Yellow
Density @15°C		kg/m <sup>3</sup>	ASTM D4052	844
Kin. Viscosity @40°C		mm²/s	ASTM D7042	27.2
Kin. Viscosity @100°C		mm²/s	ASTM D7042	5.7
Viscosity Index			<b>ASTM D2270</b>	161
Flash Point COC		°C	ASTM D92	>201
Pour Point		°C	ASTM D7346	-48
Product Nr: 4501	Date Issued: 31-10-2019	Date Superseded: 10-04-2018		Revision nr: 02