



Product Data Sheet

ATF L8S

Product Description:

ATF L8S is a synthetic high quality heavy-duty oil intended exclusively for ZF 6-speed and 8-speed automatic car transmissions. Subjected to extreme testing, ATF L8S guarantees maximum performance of the automatic transmission. At the same time, the wear of heavily loaded components is minimized due to the specifically matched oils.

ATF L8S is based on fully synthetic base in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidation stability.
- Excellent lubrication, even under extreme conditions.
- Very high protection against wear, corrosion and foam.
- High "shear stable".
- Very low Pour point, can be used by very cold temperatures.
- High Viscosity Index.

ATF L8S meets the following performance criteria:

VW G 060 162 BMW 83 22 2 152 426 BMW83 22 2 305 397 BMW 83 22 2 289 720
VW G 055 540 ATF SP-IV-RR

ATF L8S is also suitable where the following specifications are required:

M 1375.4 VW G 055 005 Toyota Type WS Nissan Matic S
Hyundai SP-IV Mercon LV Dexron VI JWS 3324

Properties	Unit	Test Method	Typical Value
Color		Visual	Colorless to light Yellow
Density @15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	27.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.7
Viscosity Index		ASTM D2270	160
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-45

Product Nr: 4504

Date Issued: 20-02-2019

Date Superseded: 10-04-2018

Revision nr: 03