

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants – Transmission Oils - Automotive

Version: 1330/02

SynPower™ CVT Fluid

Premium multi-vehicle transmission fluid for passenger cars and vans with a CVT (Continuously Variable Transmission) gearbox.

Valvoline SynPower CVT fluid provides outstanding protection and lubrication of most belt and chain-driven transmissions over a wide temperature range..

Performance Levels/Approvals

| |
|---|
| BMW / Mini Cooper EZL 799 |
| Dodge / Jeep NS-2, CVT fluid +4 |
| Ford CVT23, CVT30, Mercon C |
| GM / Saturn DEX-CVT |
| Honda HMMF |
| Hyundai / Kia SP-III (not in automatic transmissions) |
| Mercedes-Benz 236.20 |
| Mitsubishi CVT fluid J1, SP-III (not in automatic transmission) |
| Nissan NS-2 |
| Subaru Lineartronic CVT fluid |
| Suzuki TC, NS-2, CVT Green 1 |
| VW / Audi TL 52180, G 052 180 |

¹ Check owners' manual before use.

Applications

Especially for belt and chain driven continuously variable transmissions.

Suitable for European, Asian, and American passenger cars and vans.

The product is not meant for Hybrid CVT units (Toyota and Ford).

Do not mix with other transmission oils.

Features and Benefits

- Superior protection

Optimum protection against wear and tear, also under high stress working conditions.

- Breakdown resistance

Premium quality base oils and a highly balanced additive system avoid breakdown situations even after long-time use.

- Consistent viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long term multigrade advantages

- Fuel Economy properties

By smooth lubrication, the product has light fuel economy properties.

Easy oil circulation gives better cooling and with that also light fuel savings.

Product Information



A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

| SynPower CVT fluid | |
|---|-------|
| Viscosity @ 100 °C, mm ² /s, ASTM D445 | 7.2 |
| Viscosity @ 40 °C, mm ² /s, ASTM D445 | 34.5 |
| Viscosity Index, ASTM D2270 | 180 |
| Density @ 15C, kg/L, ASTM D4052 | 0.855 |
| Pour Point, °C, ASTM D5950 | -45 |

Note: SynPower CVT fluid may be unsuitable for use in some transmissions, consult owners' manual if in doubt

This information only applies to products manufactured in the following location(s): Australia

| Part Number | Pack Size |
|-------------|-----------|
| 1330.50 | 5 L |
| 1330.20 | 20 L |
| 1330.28 | 208 L |

People Who Know, Use Valvoline™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658

Author:

FM – Effective 1-04-2013

Replaces – 1330/01