



# **REKTOL OW-40 Combisynt Super Leichtlauf Motor Oil**

**Article number: 1060040 XX**

---

Rektol OW-40 Super Leichtlauf motor oil consists of a combination of the most modern Full-Synthesis and HC-Synthesis components and is suitable for petrol- and Diesel engines. The special viscosity enables a high fuel saving. Specially selected additives enable an improved wear protection and increase the service life of the engine at excellent cold start characteristics.

---

## **Specification**

SAE OW-40

API SN/CF

ACEA A3/B4

## **Rektol Recommendation**

BMW Longlife 01

MB 229.5

Porsche A 40

Renault RN 0700, 0710

VW 502.00, 505.00

---

## **User Benefits**

- excellent wear protection
  - outstanding oxidation- and temperature stability
  - low friction losses
  - optimum engine cleanliness due to excellent cleaning properties
  - long oil changing intervals
  - improved fuel efficiency
-

### Typical Characteristics

Density at 15°C	g/ml	DIN 51757	0,864
Flashpoint	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-53
Viscosity at 40 °C	mm <sup>2</sup> / sec	DIN 51562	80
Viscosity at 100 °C	mm <sup>2</sup> / sec	DIN 51562	14
Viscosityindex		DIN ISO 2909	180

---

The information in this product data sheet is based on over 100 years of experience of company Rektol GmbH & Co. KG. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our application engineer regarding the application conditions and requirements before the REKTOL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

---

### Rektol GmbH & Co. KG

Am Kniep 2 • 34497 Korbach • Telefon: +49 (0) 5631-95300 • Telefax: +49 (0) 5631-953025  
Internet: [www.rektol.de](http://www.rektol.de) • E-Mail: [info@rektol.de](mailto:info@rektol.de)