



Aral MegaSynth 5W-40

High Performance low SAPS engine oil

Description

Aral MegaSynth 5W-40 is a high performance low SAPS engine oil in Aral Synth Technology for severe driving conditions. It can be used in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C3, API SN/CF or earlier specification 5W-40 lubricant. The fluid is especially suitable for use in vehicles fitted with a DPF.

Advantages

- Superior engine cleanliness
- Comprehensive engine protection
- Prolongs the life of modern emissions systems
- Reduced harmful emissions
- Protects the DPF aftertreatment system

Typical Characteristics

Name	Method	Units	MegaSynth 5W-40
Appearance	Visual	-	Clear & Bright
Density @ 15C, Relative	ASTM D4052	g/ml	0.848
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	82
Viscosity Index	ASTM D2270	None	174
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	5550
Pour Point	ASTM D97	°C	-48
Flash Point, PMCC	ASTM D93	°C	210

Product Performance Claims

ACEA C3
API SN/CF
Porsche A40
MB-Approval 226.5/ 229.31
VW 502 00/ 505 00/ 505 01
Renault RN 0700 / RN 0710
Meets Fiat 9.55535-S2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aral MegaSynth 5W-40

24 Jun 2014

Aral, the Aral logo and related marks are trademarks of Aral Aktiengesellschaft, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Aral Aktiengesellschaft, Geschäftsbereich Schmierstoffe, Überseeallee 1, D-20457 Hamburg
01801-11 55 11
www.aral-lubricants.de