

MATERIAL SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 081070

MAZDA ORIGINAL OIL ULTRA DPF 5W-30

 Date of the previous version:
 2012-02-02
 Revision Date:
 2013-02-18
 Version
 1.01

 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
 1.1.
 Product identifier
 1.1.
 Product identifier
 1.1.
 Product name NAZDA ORIGINAL OIL ULTRA DPF 5W-30
 717
 717
 717
 Mixture
 1.2.
 Relevant identified uses of the substance or mixture and uses advised against
 1.3.
 Details of the supplier of the safety data sheet
 1.3.
 Details of the supplier of the safety data sheet
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.
 1.3.<

Supplier TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.msds-lubs@total.com

1.4. Emergency telephone number

+33 1 49 00 00 49 (24h/24, 7d/7)

France - ORFILA (INRS) Tél : +33 (0)1 45 42 59 59 In France : - PARIS : Hôpital Fernand Widal 200, rue du Faubourg Saint-Denis 75475 Paris Cédex 10 , Tel : 01.40.05.48.48. -MARSEILLE : Hopital Salvator, 249 bd Ste Marguerite 13274 Marseille cedex 5, Tel : 04.91.75.25.25. - LYON : Hopital Edouard Herriot, 5 place d'Arsonvol, 69437 Lyon cedex 3, Tel : 04.72.11.69.11. - NANCY : Hopital central, 29 Av du Mal De Lattre de Tassigny, 54000 Nancy, Tel : 03.83.32.36.36 ou le SAMU : Tel (15)

2. HAZARDS IDENTIFICATION

.

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

DIRECTIVE 67/548/EEC or 1999/45/EC

For the full text of the R-phrases mentioned in this Section, see Section 16

The substance/mixture is classified as dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments **Classification**

2.2. Label elements

Labelled according to

Directive 1999/45/EC

Hazard pictograms none

R-phrase(s)

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment***

S-phrase(s)

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets***

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties

Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture

Chemical Name	EC-No	REACH registration No	CAS-No	Weight %	Classification (Dir. 67/548)	Classification (Reg. 1272/2008)
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts***		01-2119493626-26	84605-29-8	<1.5	Xi;R38-41 N;R51-53	Aquatic Chronic 2 (H411) Eye Dam. 1 (H318) Skin Irrit. 2 (H315)
Phenol, dodecyl-, branched***	310-154-3	01-2119513207-49	121158-58-5	<0.5	Xi;R36/38 N;R50-53 Repr.Cat.3;R62	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Eye Irrit. 2 (H319) Repr. 2 (H361) Skin Irrit. 2 (H315)



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

Page 3/13

Diphenylamine***	204-539-4*	no data available	122-39-4	<0.5	T; R23/24/25	Acute Tox. 3 (H301)
	**				R33	Acute Tox. 3 (H311)
					N; R50-53	Acute Tox. 3 (H331)
					***	STOT RE 2 (H373)
						Aquatic Acute 1 (H400)
						Aquatic Chronic 1 (H410)***

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

For the full text of the R-phrases mentioned in this Section, see Section 16 For the full text of the H-Statements mentioned in this Section, see Section 16.

14	FIRST AID MEASURES	
14.		

4.1. Description of first-aid measures

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.
Inhalation	Move to fresh air.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.
4.2. Most important sympt	oms and effects, both acute and delayed
Eye contact	Not classified.
Skin contact	Not classified.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
4.3. Indication of immedia	te medical attention and special treatment needed, if necessary
Notos to physician	

Notes to physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

.



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18 Version 1.01 5.1. Extinguishing media Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog. Do not use a solid water stream as it may scatter and spread fire. **Unsuitable Extinguishing Media** 5.2. Special hazards arising from the substance or mixture **Special Hazard** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. 5.3. Advice for fire-fighters Special protective equipment for Wear self-contained breathing apparatus and protective suit. fire-fighters Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. 6. ACCIDENTAL RELEASE MEASURES 6.1. Personal precautions, protective equipment and emergency procedures **General Information** Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. 6.2. Environmental precautions **General Information** Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained. 6.3. Methods and materials for containment and cleaning up Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. 6.4. Reference to other sections **Personal Protective Equipment** See Section 8 for more detail.

Version EU



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.
Prevention of fire and explosion	Take precautionary measures against static discharges: Ground/bond containers, tanks and transfer/receiving equipment.
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical
	contacts. Protect from frost, heat and sunlight. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

7.3. Specific end uses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits oil mist : 10mg/m³, for 15 minutes oil mist : 5mg/m³, for 8 hours

Legend See section 16

DNEL Worker (Industrial/Professional)***

Chemical Name	Short term, systemic	Short term, local effects	Long term, systemic	Long term, local effects
	effects		effects	



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

Phenol, dodecyl-, branched*** 121158-58-5	166 mg/kg bw/day Dermal 44.18 mg/m³ Inhalation***		0.25 mg/kg bw/day Dermal 1.7621 mg/m³ Inhalation***	
DNEL Consumer***				
Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Phenol, dodecyl-, branched*** 121158-58-5	50 mg/kg bw/day Dermal 13.26 mg/m ³ Inhalation 1.26 mg/kg bw/day Oral***		0.075 mg/kg bw/day Dermal 0.79 mg/m ³ Inhalation 0.075 mg/kg bw/day Oral***	

Predicted No Effect Concentration *** (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Phenol, dodecyl-, branched*** 121158-58-5	0.074 μg/l fw 0.0074 μg/l mw 0.37 μg/l or***	0.226 mg/kg fw dw 0.0266 mg/kg mw dw***	0.118 mg/kg dw***		100 mg/l***	4 mg/kg food***

8.2. Exposure controls

Occupational Exposure Controls

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.		
Personal Protective Equipment			
General Information	If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.		
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.		
Eye Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields.		
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.		
Hand Protection	Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.		



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

Environmental exposure controls

General Information

The product should not be allowed to enter drains, water courses or the soil.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Color Physical State @20°C Odor		brown liquid Characteristic	
<u>Property</u> pH Boiling point/boiling range	Values	Remarks Not applicable No information available	<u>Method</u>
Flash point	228 °C 442 °F		ASTM D 92 ASTM D 92.
Evaporation rate Flammability Limits in Air Vapor Pressure Vapor density Density Water solubility Solubility in other solvents	854 kg/m³	No information available No information available No information available No information available @ 15 °C Insoluble Soluble in many common organic solvents	
logPow Autoignition temperature	> 250 °C > 482 °F	No information available	ASTM E 659-78 ASTM E 659-78
Viscosity, kinematic	10.4 - 11 mm2/s	@ 100 °C	ISO 3104
Explosive properties Oxidizing Properties Possibility of hazardous reactions	Not explosive Not applicable Not applicable		130 3104

9.2. Other information

10. STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

.

Stability

Stable under recommended storage conditions.



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

10.3. Possibility of hazardous reactions

Hazardous Reactions None under normal processing.

10.4. Conditions to Avoid

Conditions to Avoid Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

10.5. Incompatible Materials

Materials to Avoid Strong oxidizing agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products None under normal use.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact	. Not classified.
Eye contact	. Not classified.
Inhalation	. Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts***	= 2000 mg/kg (Rat)	> 3200 mg/kg (Rabbit)	
Phenol, dodecyl-, branched***	LD50 2100 mg/kg (Rat-OECD 401) ***	LD50 15000 mg/kg (Rabbit-OECD 402)***	
Diphenylamine***	= 1165 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	

Sensitization

Sensitization

Not classified as a sensitizer.

Specific effects



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

This product is not classified carcinogenic. During use in engines, co low levels of combustion products occurs. Used motor oils have been cancer in mice following repeated application and continuous exposu skin contact with used motor oil is not expected to have serious effect is thoroughly removed by washing with soap and water.	n shown to cause skin ure. Brief or intermittent
1 5	hazards.
No information available.	
No information available.	
Characteristic skin lesions (pimples) may develop following prolonge exposures (contact with contaminated clothing).	ed and repeated
	low levels of combustion products occurs. Used motor oils have bee cancer in mice following repeated application and continuous exposi- skin contact with used motor oil is not expected to have serious effec- is thoroughly removed by washing with soap and water. This product is not classified as mutagenic. This product does not present any known or suspected reproductive No information available. No information available. Characteristic skin lesions (pimples) may develop following prolonge

12. ECOLOGICAL INFORMATION

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts*** 84605-29-8		EC50 (48h) 0.1 - 1 mg/L Daphnia magna	LC50 (96h) 10-100 mg/L Pimephales promelas (static) LC50 (96h) > 100 mg/L Pimephales promelas (semi-static)	
Phenol, dodecyl-, branched*** 121158-58-5	EC50(72h) 0.26-0.50 mg/l Desmodesmus subspicatus static (OECD 201)***	EC50(48h) 0.037 mg/l Daphnia magna static (OECD 202)***	EL50(96h) 40 mg/l Pimephales promelas semi-static (OECD 203)***	
Diphenylamine*** 122-39-4	EC50 (72h) = 1.5 mg/l Scenedesmus subspicatus	EC50 (48h) 1.69 - 2.46 mg/L Daphnia magna	LC50 (96h) 3.47-4.14 mg/L Pimephales promelas (flow-through)	EC50 = 4.77 mg/L 30 min EC50 = 2.81 mg/L 5 min EC50 = 3.46 mg/L 15 min

Chronic aquatic toxicity • Product Information

.

No information available.

Chronic aquatic toxicity - Component Information



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Phenol, dodecyl-,		NOEC(21d) 0.0037 mg/l		
branched***		Daphnia magna semi-static		
121158-58-5		(OECD 211)***		

Effects on terrestrial organisms

No information available.

12.2. Persistence and degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information

No information available.

logPow

No information available

Component Information	
-----------------------	--

Chemical Name	log Pow
Phenol, dodecyl-, branched*** - 121158-58-5	7.1
Diphenylamine*** - 122-39-4	3.4***

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.
Air	Loss by evaporation is limited.
Water	Insoluble. The product spreads on the surface of the water.
12.5. Results of PBT and v	PvB assessment
PBT and vPvB assessment	No information available.

12.6. Other adverse effects

General Information No information available.

13. DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

	Revision Date: 2013-02-18	Version	1.01
Waste from Residues / Unused Products	Should not be released into the environment. Dispose of in accordance Directives on waste and hazardous waste. Dispose of in accordance w Where possible recycling is preferred to disposal or incineration. After u sent to a licensed waste oil facility. Incorrect disposal of used oil poses environment. Mixture with other waste types such as solvents, brake- a forbidden.	ith local regulati use, this oil mus a risk to the	ions. st be
Contaminated packaging	Empty containers should be taken to an approved waste handling site t disposal.	for recycling or	
EWC Waste Disposal No.	The following Waste Codes are only suggestions:. 13 02 05. According Waste Catalogue, Waste Codes are not product specific, but applicatio codes should be assigned by the user based on the application for whit used.	n specific. Wast	te
14. TRANSPORT INFORMA	TION		
ADR/RID	Not regulated		
IMDG/IMO	Not regulated		

ADN Not regulated

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not regulated

European Union

ICAO/IATA

International Inventories

EINECS/ELINCS	-
TSCA	-
DSL	-
ENCS	-
IECSC	-
KECL	-
PICCS	-

· · · · · · · · ·



MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

AICS NZIoC

Legend

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

-

AICS - Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

Further information

15.2. Chemical Safety Assessment

Chemical Safety Assessment

No information available

16. OTHER INFORMATION

Full text of R-phrases referred to under sections 2 and 3

R41 - Risk of serious damage to eyes

R38 - Irritating to skin

R62 - Possible risk of impaired fertility

R33 - Danger of cumulative effects***

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R36/38 - Irritating to eyes and skin

R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed

R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment***

Full text of H-Statements referred to under sections 2 and 3

- H301 Toxic if swallowed
- H311 Toxic in contact with skin
- H315 Causes skin irritation
- H318 Causes serious eye damage
- H319 Causes serious eye irritation
- H331 Toxic if inhaled
- H373 May cause damage to organs through prolonged or repeated exposure
- H361f Suspected of damaging fertility

.

- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects
- H411 Toxic to aquatic life with long lasting effects***

Abbreviations, acronyms



.

MAZDA ORIGINAL OIL ULTRA DPF 5W-30

Revision Date: 2013-02-18

Version 1.01

Legend Sec	tion 8		
+	Sensitizer	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

 Revision Date:
 2013-02-18

 Revision Note
 *** Indicates updated section.

 This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet