

Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL **DEUTSCHLAND**

info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS07 GHS08 GHS09

· Signal word Danger

(Contd. on page 2)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 1)

· Hazard-determining components of labelling:

2-ethylhexyl nitrate

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)

Hydrocarbons, C10 aromatics, <1% naphthalene

· Hazard statements

H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P330 Rinse mouth.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage. P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
2-ethylhexyl nitrate	10-<37.5%		
Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332			
EC number: 925-653-7 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Asp. Tox. 1, H304; Aquatic Chronic 3, H412			
EC number: 920-360-0 Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)			
Asp. Tox. 1, H304			
EC number: 918-811-1 Hydrocarbons, C10 aromatics, <1% naphthalene			
Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336			
	2-ethylhexyl nitrate Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Asp. Tox. 1, H304; Aquatic Chronic 3, H412 Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %) Asp. Tox. 1, H304 Hydrocarbons, C10 aromatics, <1% naphthalene		

(Contd. on page 3)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2. Do not use water.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 4)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 3)

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION	I 9. Physica	I and chemical	nronartias
SECTION	ı J. FIIVSICA	i allu Clitillicai	DIODELLES

SECTION 9. Physical and chemi	cai properties
• 9.1 Information on basic physical and of General Information	chemical properties
Appearance:	ELZI
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
· Flash point:	76.1 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 5)

· Solvent content:

VOC (EC) 0.00 %

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:				
MANNOL	MANNOL 9988 Super Diesel Cetan Plus 455ml			
Oral	LD50	>1,333–5,000 mg/kg		
Dermal	LD50	>13.3–20 mg/kg		
Inhalative	LC50/4 h	>17.5–41.1 mg/l		
Hydrocar	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Oral	LD50	15,000 mg/kg (rat)		
Dermal	LD50	4 mg/kg (rat)		
Inhalative	LC50/4 h	13.1 mg/l (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 6)

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP14 Ecotoxic

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

				T		
	3 64 1	\mathbf{n}	14'	Transport	- 11	ľΙΛΝ
_			-	Hallopoli	-	поп

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN3313

14.2 UN proper shipping name

· ADR 3313 ORGANIC PIGMENTS, SELF-HEATING ORGANIC PIGMENTS, SELF-HEATING

(Contd. on page 8)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 7) · 14.3 Transport hazard class(es) · ADR · Class 9 Miscellaneous dangerous substances and articles. · Label · IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles. · Label 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: Product contains environmentally hazardous substances: Hydrocarbons, C10 aromatics, <1% naphthalene · Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. · Hazard identification number (Kemler code): 40 · EMS Number: F-A,S-J Stowage Category Ε · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 0 Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 0 Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Contd. on page 9)



Printing date 05.08.2020 Version number 1 Revision: 14.07.2020

Trade name: MANNOL 9955 Super Diesel Cetan Plus 500ml

(Contd. of page 8)

• UN "Model Regulation": UN 3313 ORGANIC PIGMENTS, SELF-HEATING,

9, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.