



L'huile des records du monde

LUBE V - SAE 0W-20

Fuel economy synthetic engine oil

APPLICATIONS

YACCO LUBE V 0W-20 is a low viscosity synthetic lubricant recommended for the latest generations of engines.

Particularly suitable to Drive-E VOLVO engines (4 cylinders gasoline and diesel from 2013), when the manufacturer recommends the use of a **VOLVO VCC RBSO-2AE 0W-20** oil.

LUBE V 0W20 is also convenient for any other type of engine when the manufacturer recommends the use of a SAE 0W-20 ACEA A1/B1 oil.

MAIN PHYSICAL DATA

		Units	0W-20
Density at	20° C	kg/m ³	842
Kinematic viscosity at	40° C	mm ² /s	46.5
Kinematic viscosity at	100° C	mm ² /s	8.9
Viscosity index			175
Flash point Cleveland open cup		°C	200
Pour point		° C	- 45
Dynamic viscosity at	- 35° C	mPa.s	5700

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- SAE 0W20 low viscosity provides quick oil flow, increased fuel economy and reduced exhaust gas emissions (CO₂, NO_x, particulates...), whilst maintaining an excellent engine protection against wear.
- Lower levels of ash, sulphur and phosphorous for a longer lifetime of particulate filters and catalytic converter systems
- Good detergent/dispersant properties keep engines clean
- Excellent shear stability, in accordance with VOLVO viscosities requirement at 100 °C and 150 °C
- Specific formula providing high protection under the most severe service conditions: city traffic, long journey, motorway...

APPROVALS

VOLVO VCC RBSO-2AE 0W20

SPECIFICATIONS

ACEA A1/B1