



L'huile des records du monde

## VX 100 - SAE 15W-40

**Top-of-the-range mineral oil for performing gasoline and Diesel engines**

### APPLICATIONS

Formulated to meet any kind of driving conditions with no particular constraint: road, highway, city traffic.

Provides excellent lubrication and year-round protection to turbocharged or normally aspirated Gasoline and Diesel engines. Compatible with catalytic converters.

### MAIN PHYSICAL DATA

		Units	15W-40
Density at	20° C	kg/m <sup>3</sup>	874
Kinematic viscosity at	40° C	mm <sup>2</sup> /s	104
Kinematic viscosity at	100° C	mm <sup>2</sup> /s	14.5
Viscosity index			143
Pour point		° C	- 33
Flash point Cleveland open cup		°C	220
Dynamic viscosity at	- 20° C	mPa.s	6200

The data given in this table are typical production values and cannot be considered as specifications

### PROPERTIES & AVANTAGES

- \*SAE 15W-40 grade is recommended for year-round lubrication
- \*Outstanding anti-wear action exceeding ACEA A3/B3-04 and API SL/CF requirements
- \*Excellent detergent and dispersant properties keeps both gasoline and Diesel engines clean
- \*Outstanding oxidation resistance keeps excellent lubricant characteristics until the next drain
- \*Reduces frictions and extends the engine life

### SPECIFICATIONS

**ACEA A3/B3**

**API SL/CF**

**VX 100 SAE 15W-40** exceeds the performances required by API and ACEA.