



L'huile des records du monde

## VX 1000 LL - SAE 5W-40

Longlife synthetic oil for gasoline, Diesel and LPG engines

### APPLICATIONS

Perfectly adapted and recommended for **heavy strained gasoline engines** (multivalve, turbo-charged-or-not) and direct injection\* turbo-charged or not **Diesel engines**.

Can be used under the **most severe operating conditions** (motorways, dense city traffic, etc.).

Adapted to all vehicles fitted with catalytic converter and/or using LPG.

### MAIN PHYSICAL DATA

|                                |         | Units              | 5W-40 |
|--------------------------------|---------|--------------------|-------|
| Density at                     | 20° C   | kg/m <sup>3</sup>  | 853   |
| Kinematic viscosity at         | 40° C   | mm <sup>2</sup> /s | 92    |
| Kinematic viscosity at         | 100° C  | mm <sup>2</sup> /s | 15    |
| Viscosity index                |         |                    | 172   |
| Flash point Cleveland open cup |         | ° C                | 230   |
| Pour point                     |         | ° C                | - 45  |
| Dynamic viscosity at           | - 30° C | mPa.s              | 5900  |

The data given in this table are typical production values and cannot be considered as specifications

### PROPERTIES & ADVANTAGES

- Synthetic lubricant, « the supreme of the SAE 5W40 oils »
- Excellent high temperature stability and shear resistance
- Outstanding performance at low temperatures
- Excellent detergent and dispersant properties
- Preserves the engine's performance and durability
- Instant protection against engine start-up wear
- Keeps engine clean, even under extremely severe operating conditions

### APPROVALS

API SN

BMW Longlife-01 ; MB-Approval 229.5

Porsche A40 ; VW 502.00 / 505.00

### SPECIFICATIONS

ACEA A3/B4; API CF

FIAT 95535 H2/M2/N2/Z2

GM-LL-B-025 ; PSA B71 2296

Renault RN 0710/0700

**VX 1000 exceeds widely** the performances required by most European OEM and the API & ACEA specifications.

\* for **VW group Diesel engines with pump-injector**, please use a VW approved oil : VW507.00 or VW505.01 depending on model and year of the vehicle.



005-LAB/FT/EE/26-2014/3027

[contact@yacco.com](mailto:contact@yacco.com)

Before using this lubricant, take a look to the car booklet to check the technical requirements of the manufacturer.