



L'huile des records du monde

VX 1500 - SAE 0W-30

Fuel economy 100 % synthetic lubricant for performing gasoline and Diesel engines

APPLICATIONS

100% synthetic fuel economy engine oil reducing exhaust emissions of passenger cars. Suitable for gasoline and Diesel engines, including those equipped with direct injection systems and turbo.

Particularly recommended when the manufacturer specifies the use of SAE 0W-30 and ACEA A5/B5, ACEA A1/B1 or API SL oils: Volvo, Toyota, Mitsubishi, Honda...

MAIN PHYSICAL DATA

		Units	0W-30
Density at	20° C	kg/m ³	842
Kinematic viscosity at	40° C	mm ² /s	53
Kinematic viscosity at	100° C	mm ² /s	10
Viscosity index			179
Flash point Cleveland open cup		° C	> 220
Pour point		° C	- 45
Dynamic viscosity at	- 35° C	mPa.s	5500

The data given in this table are typical production values and cannot be considered as specifications

PROPERTIES & ADVANTAGES

- 100% synthetic formulation providing outstanding thermal resistance, and excellent lubrication in all driving conditions: road, highway, city traffic. Allows extended drain intervals.
- Low HTHS viscosity at 150°C (low viscosity at high temperature under high shear). This helps to protect the environment by lowering the fuel consumption and reducing exhaust emissions.
- Low viscosity in cold condition (100% synthetic SAE 0W-30 oil) provides instant oil flow for increase engine protection and reduced engine wear.
- Excellent detergent/dispersant properties keep the engine clean, even under severe service condition

APPROVAL

VOLVO VCC 95200377

SPECIFICATIONS

ACEA A5/B5 (exceeds ACEA A1/B1)

API SL