



L'huile des records du monde

VX 2000 - SAE 0W-30

100% synthetic "longlife" and fuel economy oil for highly performing gasoline and Diesel engines

APPLICATIONS

Exclusively formulated to cover the most stringent requirements of gasoline and Diesel engines (from 2000 to 2007) with WIV (long drain intervals) of VW group (Audi, Seat, Skoda, Volkswagen) which require VW 503.00 (gasoline), VW 506.00 (Diesel) or **VW 506.01** standard (pump injector Diesel).

Suitable for turbocharged engines (including new Diesel direct injection technologies), multivalve, fitted with catalytic converter, **when the manufacturer requires an ACEA A5/B5-07 or ACEA A1/B1-07 lubricant**. Can be used all year in the most difficult operating conditions (motorways, dense city traffic, etc.).

MAIN PHYSICAL DATA

		Units	0W-30
Density at	20° C	kg/m ³	853
Kinematic viscosity at	40° C	mm ² /s	53
Kinematic viscosity at	100° C	mm ² /s	9.6
Viscosity index			167
Pour point		° C	- 54
Flash point Cleveland O.C.		° C	223
Dynamic viscosity at	- 35° C	mPa.s	< 6200

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- Exceptional resistance to **oxidation to keep the oil properties in the long term**
→ Satisfies the most stringent OEM maintenance conditions (**extended drain intervals**)
- Low viscosity at cold temperature
→ Ensures **easy start-up** while maintaining a very resistant oil film, even at high temperature
- Optimal **protection** of mechanical parts
→ Preserves **the engine power** and its lifetime
- Significant **reduction of fuel consumption**
→ Contributes to **protect the environment** by reducing the polluting emissions

SPECIFICATIONS

VW 503.00 (gasoline) / VW 506.00 (Diesel) / VW 506.01 (Injector-pump Diesel)
ACEA A5/B5-07

For recent VW group engines requiring only VW 504.00 or VW 507.00 oil, please use only YACCO LUBE DE 5W-30 or YACCO VX 2103 FAP 5W-30.

Please note that for R5 Diesel and V10 TDI engines (up to 2007) requiring only VW 506.01 standard, you must use our VX 2000 0W-30.

After 2007 the recommendations have changed and the new recommendation is VW 507.00 (YACCO VX 2103 FAP 5W-30 or LUBE DE 5W-30)

