



L'huile des records du monde

GALAXIE RS - SAE 0W-40

100% synthetic racing oil

APPLICATIONS

This PAO based 100% synthetic lubricant is designed to ensure optimal engine lubrication under extreme conditions.

For highly stressed sport engines used on road or circuits.

Initially developed for gasoline engines, turbocharged-or-not, multivalve-or-not, this lubricant is also suitable for Diesel engines without DPF (Diesel Particulate Filter).

Also suitable for engines where manufacturers recommend or specify the use of an SAE 0W-40 FORD WSS-M2C937-A (Ford Focus RS) or ACEA A3/B4, API SN engine oil.

MAIN PHYSICAL DATA

		Units	0W-40
Density at	20° C	kg/m ³	840
Kinematic viscosity at	40° C	mm ² /s	13,6
Kinematic viscosity at	100° C	mm ² /s	77.5
Viscosity index			181
Pour point		° C	- 51
Flash point Cleveland open cup		°C	228
Dynamic viscosity at	- 30°C	mPa.s	5900

The data given in this table are typical production values and cannot be considered as specifications.

PROPERTIES & ADVANTAGES

- The grade SAE 0W40 provides excellent engine protection at start-up and helps fuel economy.
- **Excellent shear resistance ensuring a continuous lubrication** at hot temperature even under severe service conditions
- **Reinforced thermal stability** to prevent the formation of deposits
- Very low volatility to reduce oil consumption
- Outstanding detergent-dispersant properties keeping the engine clean

SPECIFICATIONS

Ford WSS-M2C937-A
ACEA A3/B4, API SN
MB 229.5, PORSCHE A40