

OEM-LINE VW LL-03 5W30

HIGH PERFORMANCE SYNTHETIC ENGINE OIL

DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- High and very stable viscosity index.
- Superior resistance against shearing.
- Fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Low SAPS / DPF- compatible.

APPLICATION

Suitable for both turbocharged and normally aspirated engines to ensure maximum economy and reduced emissions (CO₂). LOW SAPS technology. Specially designed to optimum performance in today's VW-Group engines where VW 507.00/504.00 specifications are required.

Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.



TYPICALS

Density at 15 °C, kg/l	0,851
Viscosity -30 °C, mPa.s	5950
Viscosity 40 °C, mm²/s	69,20
Viscosity 100 °C, mm²/s	12,00
Viscosity Index	171
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	6,7
Sulphate Ash, %	0,67

SPECIFICATIONS

ACEA C3
VW 504.00/507.00
MB-Approval 229.51
BMW LL-04
Porsche C30

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum