

OEM-LINE FORD 913-D 5W30

HIGH PERFORMANCE SYNTHETIC BASED LOW SAPS OIL

DESCRIPTION

A modern, synthetic based, fuel economy universal motor oil, produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- High and very stable viscosity index.
- Superior resistance against shearing.
- Fast cold start.
- Very strong resistance against oxidation.
- Safe lubrication film at all temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Low SAPS – DPF compatible.



APPLICATION

Specially designed to optimum performance in today's Ford-Group engines where Ford WSS-M2C913-D specs are required. This oil is fully backwards compatible with Ford M2C 913-A, B and C.

Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

Warning: This oil has the lowest SAPS limits and may be unsuitable for use in some older or non-automotive engines.

TYPICALS

Density at 15 °C, kg/l	0,853
Viscosity -30 °C, mPa.s	4200
Viscosity 40 °C, mm./s	53,30
Viscosity 100 °C, mm./s	9,66
Viscosity Index	168
Flash Point COC, °C	220
Pour Point, °C	-45
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,09

SPECIFICATIONS

API SL/CF
ACEA A1/B1, A5/B5
Ford WSS-M2C913-D

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum