



KOKYBĖS SERTIFIKATAS
CERTIFICATE OF QUALITY · ПАСПОРТ КАЧЕСТВА

Print date: 2021-01-13

1. Product identifier:

Engine oil
MANNOL 7722 LONGLIFE 508/509 0W-20, Volume: 1 l

2. Product manufacturing date:

2020-12-02

Batch №

H-8938

Expiry date

12.2025

3. Handling and storage:

Store in a dry, cool place with sufficient ventilation. Keep out of direct sunlight. Storage room do not smoke. Keep out of children. For more information see the safety data sheet.

4. Product quality parameters:

MANNOL 7722 LONGLIFE 508/509 0W-20			
Product specification	SAE 0W-20 API SP (RC) ACEA C5 VW 508.00 VW 509.00, PORSCHE C20 MB 229.71 BMW LL-17FE+, VOLVO VCC RBSO-2AE (Service Fill) OPEL OVO401547 GM dexos1 Gen2		
Parameter name	Standard	Results	Test method
Viscosity at 100°C, cSt	7-9,5	8.94	ASTM D-445
Viscosity at 40°C, cSt	-	47.47	ASTM D-445
Viscosity index, min	160	172	ASTM D-2270
Dynamic viscosity [cP], at -35°C, max	6200	6100	ASTM D-5293
Total base no. mgKOH/g, min	9,5	9.60	ASTM D-2896
Flash point, open cup, °C	220	224	ASTM D-92
Pour point, °C, max	-40	-46	ASTM D-97
Density at 15°C, kg/l, max	0,9	0,83	ASTM D-1298
High-shear-rate viscosity, cP at 150°C, min	>2,6	2,76	ASTM D-4741

Responsible for analysis: Alicija Sokolova

UAB "SCT LUBRICANTS"

ŠILUTĖS PL. 119, LT 95112 KLAIPĖDA, LIETUVA
TEL (8 46) 34 03 45, FAKS (8 46) 34 18 91
E-MAIL: KLAIPEDA@SCT.LT