

## **TECHNICAL CHARACTERISTICS**

**SELENIA MULTIPOWER**

**PRODUCT CODE: 1046**

### **APPLICATION**

Synthetic oil that provides the best protection and efficiency overall for the latest generation of gasoline and alternative engines (methane and LPG). Developed to warrant the utmost fuel saving.

### **SPECIFICATIONS**

SAE 5W-30, ACEA A1/A5, API SL,  
FIAT 9.55535-G1 CONTRACTUAL TECHNICAL REFERENCE N°F315.B04, GM-LL-A-025

### **TEST DESCRIPTION**

| TEST DESCRIPTION      | METHOD      | UNIT              | TYPICAL VALUE |
|-----------------------|-------------|-------------------|---------------|
| APPEARANCE            | --          | --                | B. & C.       |
| DENSITY 15°C          | ASTM D4052  | g/cm <sup>3</sup> | 0,852         |
| VISCOSITY @ 100°C     | ASTM D 445  | cSt               | 10,0          |
| VISCOSITY INDEX       | ASTM D 2270 | --                | 166           |
| FLASH POINT Cl. O. C. | ASTM D 92   | °C                | >200          |
| T.B.N.                | ASTM D 2896 | mg KOH/g          | 10,3          |
| POUR POINT            | ASTM D 97   | °C                | <-36          |
| FOAM @ 24°C           | ASTM D 892  | cc/s              | TRACES/0      |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

01/2014