



ERIS 5W 30



BESCHREIBUNG:

ERIS is high performance engine lubricant fluid formulated from a fully synthetic base and strictly selected additives in order to grant maximum engine performance.

The choice of fully synthetic base PAO (poly-alfa-olefine) provides outstanding thermal stability and oxidation resistance, as well as exceptional lubrication characteristics which assure friction reduction and consequently fuel consumption containment (fuel economy).

Thanks to its particular formulation ERIS 5W30 provides maximum performance over a wide working temperature range and prolonged oil change interval.

Particular low SAPS additives (low ashes, low sulphur and low phosphorus content) assures perfect engine and catalyst system cleanness and outstanding lubrication properties of ERIS contribute to significant mechanical parts wear reduction.

ANWENDUNGEN:

ERIS is high performance engine oil particularly formulated for DIESEL engines with catalyst and/or diesel particulate filter (DPF).

ERIS is likewise indicated for dated vehicle fleets where SAE 5W30 oil is prescribed.

TECHNISCHE ANGABEN - ZULASSUNGEN:

ACEA C4

RENAULT RN 720

MB 229.51

ANWENDUNGSBEREICHE:



VERPACKUNG

Flacone : 1lt

Latta : 18kg

Fustino : 50kg

Fusto : 180kg

TYP

Olio PAO : ✓

TECHNISCHE DATEN

SAE : 5W / 30

ACEA : C4

Mercedes : MB 229.51

Viscosità DIN 51562 40°C : 68

Viscosità DIN 51562 100°C : 11,6

Viskositätsindex ISO 2909 : 164

Dichte 15°C DIN 51757 Kg/dm3 : 0,85

TBN mg KOH/g: 7

Temperatura minima pompabilità °C: -33

IMPIEGHI

Motore : ✓