

PRODUCT **DATA SHEET**AUTOMOTIVE

Millers Oils Ltd, Brighouse, West Yorkshire HD6 3DP UK Tel: +44(0)1484 713201 Visit: millersoils.co.uk

Product Code: 7706 Print Product Data

PRODUCT NAME/VISCOSITIES

EE LONGLIFE ECO 5w30

DESCRIPTION

A fully synthetic high performance, low friction, fuel efficient engine oil. Part of the Millers Oils NANODRIVE Low Friction Technology range. Formulated to meet the demanding requirements of today's engines with the added benefits of reduced friction, improved fuel economy and a reduction in overall running costs.

APPLICATION

Suitable for use in the very latest Ford petrol and diesel engines meeting Euro IV / V emission standards. The Millers Oils NANODRIVE Low Friction Technology provides the following benefits:

USER BENEFITS

- A reduction in friction of up to 53% providing a reduction in wear of up to 50% compared to other 5w30 ECO grades. Backwards compatible with previous M2C913-B and C specifications.
- The coefficient of friction reduces rapidly as the engine temperature rises, maximising fuel economy and reduces emissions accordingly.
- Protects against wear, extending engine component life.
- · Overall running costs are reduced through lower fuel consumption and longer component life.

PERFORMANCE PROFILE

ACEA: A5 / B5API: SL, CF

• FORD: M2C913-D, M2C913-C, M2C913-B

• Renault: RN0700

• Jaguar Land Rover: STJLR 03.5003

TYPICAL CHARACTERISTICS

SAE Viscosity	5w30
Specific Gravity (at 15°C)	0.858
Kinematic Viscosity (at 100°C, cSt)	11.25
Kinematic Viscosity (at 40°C, cSt)	67.9
Viscosity Index	159
Pour Point (°C)	-42
Flash Point (°C)	>200
Cold Crank Viscosity (cP)	6,600

HEALTH & SAFETY

We are in the process of preparing new MSDS files to comply with new legislation. If you need an MSDS please contact us.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Last Modified: 05/12/2014. All the data contained herein was correct at the time of last modification.