

# LUKOIL GENESIS ADVANCED 10W-40

Product number: 563040

**Semi-synthetic multigrade engine oil for gasoline and diesel engines**

## APPROVALS

API SN

## MEETS REQUIREMENTS

ACEA A3/B4, A3/B3

API CF

Fiat 9.55535-G2

MB 229.3

Opel GM LL-A, B-025

PSA B71 2294, B71 2300

Renault RN 0700, RN 0710

VW 502 00/ 505 00

## PRODUCT DESCRIPTION

**LUKOIL GENESIS ADVANCED 10W-40** is a semi-synthetic multigrade engine oil for today's gasoline and diesel engines without diesel particulate filter. It permits severe operating and traffic conditions and thereby guarantees full reliability.

**LUKOIL GENESIS ADVANCED 10W-40** winter viscosity reduces friction during cold operation.

**LUKOIL GENESIS ADVANCED 10W-40** stable summer viscosity reaches every part of the engine and guarantees highest security during urban stop-and-go traffic.

**LUKOIL GENESIS ADVANCED 10W-40** is qualified for turbo-charged engines and catalytic converters and provide high reserves in performance within the recommended oil drain interval.

**LUKOIL GENESIS ADVANCED 10W-40** low volatility reduces oil consumption.

## APPLICATION

**LUKOIL GENESIS ADVANCED 10W-40** can be used in older car, gasoline and diesel engines without DPF.

**LUKOIL GENESIS ADVANCED 10W-40** can be mixed with other branded oils with the same specification level. The full range of performance is only guaranteed if it is not mixed.

For detailed information about your vehicle's lubrication and specifications, please refer to the manufacturer's user manual.

Aug. 24, 21, Page 1/2

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service [technics.lubes@eu.lukoil.com](mailto:technics.lubes@eu.lukoil.com).

## **TYPICAL TEST DATA**

Property	Unit	Test method	LUKOIL GENESIS ADVANCED 10W-40
Density @ 15°C	kg/m <sup>3</sup>	DIN 51757	858
Flash point (COC)	°C	ISO 2592	≥220
Viscosity class	---	SAE J 300	10W-40
Viscosity @ 40°C	mm <sup>2</sup> /s	DIN 51562/T1	80,7
Viscosity @ 100°C	mm <sup>2</sup> /s	DIN 51562/T1	13,1
Viscosity index	---	DIN ISO 2909	164
Pour point	°C	DIN ISO 3016	≤-33
Total Base Number	mg KOH / g	ASTM D2896	10.9

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

## **SHELF LIFE AND STORAGE**

When stored in the original unopened containers in a dry place, this product has a shelf life of at least 60 months from the date of production.

## **SAFETY, HEALTH, ENVIRONMENT**

This product doesn't contain any toxic ingredients. During storage, transportation and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed.

For further information on how to use LUKOIL products, please refer to the material safety data sheet:

<http://www.lukoil-lubricants.eu/>