

LUKOIL GENESIS SPECIAL C3 5W-30

Product number: 563104

Synthetic engine oil for gasoline and diesel engines with DPF

APPROVALS

API SN
GM dexos2™-licensed D20271HC072
MB-Approval 226.5 (pending)
MB-Approval 229.51/ 229.52
Renault RN 0700/ 0710

MEETS REQUIREMENTS

ACEA C2, C3
API CF
BMW LL-04
Fiat 9.55535-S3
MB 229.31
PSA B71 2290

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL C3 5W-30 is a synthetic engine oil for up-to-date gasoline and diesel engines with particulate filter. It offers high reliability and allows maximum reduction of fuel consumption. The Mid SAPS-Level protects the environment as well as the particulate filter because of the low content of sulphated ash, phosphor and sulphur.

LUKOIL GENESIS SPECIAL C3 5W-30 minimized oil related emissions and guarantees maximum protection of the environment.

LUKOIL GENESIS SPECIAL C3 5W-30 reduced ash formula provide Long durability of particulate filter.

LUKOIL GENESIS SPECIAL C3 5W-30 latest additive technology keeps engine clean, reduces friction and guarantees maximum engine lifetime.

LUKOIL GENESIS SPECIAL C3 5W-30 provide long oil drain intervals and thereby high economy.

APPLICATION

LUKOIL GENESIS SPECIAL C3 5W-30 can be used in many newer passenger cars, gasoline and diesel engines with DPF, especially for BMW, Mercedes Benz, Opel.

LUKOIL GENESIS SPECIAL C3 5W-30 is recommended to use in LPG (Liquefied Petroleum Gas) engines requiring Mid SAPS engine oils.

LUKOIL GENESIS SPECIAL C3 5W-30 can be mixed with other branded oils with the same specification level. But the full range of performance is only guaranteed if used pure.

For detailed information about your vehicle's lubrication and specifications, please refer to the manufacturer's user manual.

21 August 2020, Page 1/2

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service technics.lubes@eu.lukoil.com.

LUKOIL Lubricants Europe
GmbH
Uferstrasse 8
1220 Vienna, Austria

+43(1)205 222-8800

www.lukoil-lubricants.eu

member of:



TYPICAL TEST DATA

Property	Unit	Test method	LUKOIL GENESIS SPECIAL C3 5W-30
Density @ 15 °C	kg/m ³	DIN 51757	843
Flash point (COC)	°C	ISO 2592	≥230
Viscosity class	---	SAE J300	5W-30
Viscosity @ 40°C	mm ² /s	DIN 51562/T1	64,7
Viscosity @ 100°C	mm ² /s	DIN 51562/T1	11,4
Viscosity index	---	DIN ISO 2909	172
Pour point	°C	DIN ISO 3016	≤-39
Total Base Number (TBN)	mg KOH / g	ASTM D2896	8,0
Sulfate ash	% mass	DIN 51575	≤0,8

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

SHELF LIFE AND STORAGE

When stored in the original unopened containers in a dry place, this product has a shelf life of at least 60 months from the date of production.

SAFETY, HEALTH, ENVIRONMENT

This product doesn't contain any toxic ingredients. During storage, transportation and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed. For further information on how to use LUKOIL products, please refer to the material safety data sheet:

<http://www.lukoil-lubricants.eu/>