

# LUKOIL GENESIS SPECIAL 5W-40

Product number: 563002

**synthetic fuel economy engine oil for gasoline and diesel engines**

## APPROVALS

API SN  
BMW LL-01  
MB-Approval 226.5  
MB-Approval 229.5  
Porsche A40  
VW 502 00/ 505 00

## MEETS REQUIREMENTS

ACEA A3/B4, A3/B3  
API CF  
Fiat 9.55535 – N2/ Z2  
MB 229.3  
Opel GM-LL-B-025  
Renault RN 0710/ 0700  
PSA B71 2296

## PRODUCT DESCRIPTION

**LUKOIL GENESIS SPECIAL 5W-40** is a synthetic fuel economy engine oil for gasoline and diesel engines without diesel particular filter. It offers best lubrication and thus highest reserves of operational safety and performance.

**LUKOIL GENESIS SPECIAL 5W-40** allows most severe operational conditions and extremely high engine operating reliability.

**LUKOIL GENESIS SPECIAL 5W-40** reduces friction of moving parts and guarantees highest economic efficiency – reduces fuel consumption.

**LUKOIL GENESIS SPECIAL 5W-40** excellent low temperature properties allows quick start-up at low temperatures.

**LUKOIL GENESIS SPECIAL 5W-40** excellent wear protection increases engine life and long oil drain intervals.

## APPLICATION

**LUKOIL GENESIS SPECIAL 5W-40** can be used in nearly every older car, gasoline and diesel engines without DPF, especially for BMW, Mercedes Benz, Opel und Volkswagen.

Mar. 12, 20, Page 1/2

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@eu.lukoil.com](mailto:technics.lubes@eu.lukoil.com)

LUKOIL Lubricants Europe  
GmbH  
Uferstrasse 8  
1220 Vienna, Austria

+43(1)205 222-8800

[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of:



## TYPICAL TEST DATA

Property	Unit	Test method	LUKOIL GENESIS SPECIAL 5W-40
Density @ 15°C	kg/m <sup>3</sup>	DIN 51757	844
Flash point COC	°C	ISO 2592	230
Viscosity class	---	SAE J 300	5W-40
Viscosity @ 40°C	mm <sup>2</sup> /s	DIN 51562/T1	83,9
Viscosity @ 100°C	mm <sup>2</sup> /s	DIN 51562/T1	13,85
Viscosity index	---	DIN ISO 2909	170
Pour point	°C	DIN ISO 3016	<-36

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

## SAFETY, HEALTH, ENVIRONMENT

This product doesn't contain any toxic ingredients. During storage, transportation and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed.

For further information on how to use LUKOIL products, please refer to the material safety data sheet:

<http://www.lukoil-lubricants.eu/>

Mar. 12, 20, Page 2/2

\* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service Lubricants [technics.lubes@eu.lukoil.com](mailto:technics.lubes@eu.lukoil.com)

LUKOIL Lubricants Europe  
GmbH  
Uferstrasse 8  
1220 Vienna, Austria

+43(1)205 222-8800

[www.lukoil-lubricants.eu](http://www.lukoil-lubricants.eu)

member of:

