

LUKOIL GENESIS SPECIAL RN 5W-30

Product number: 563124

Synthetic low SAPS engine oil to meet the latest requirements for Renault

APPROVALS

RENAULT RN17

MEETS REQUIREMENTS

ACEA C3

PRODUCT DESCRIPTION

LUKOIL GENESIS SPECIAL RN 5W-30 is a synthetic low SAPS engine oil, especially developed for the latest generation of Renault diesel and gasoline engines. This innovative premium product has been tailor-made to offer Renault and Dacia customers the best quality and performance for their car.

This engine oil is compatible with all latest generation after treatment systems.

- Perfect engine cleanliness and wear protection as a result of the latest additive technology
- Guarantees maximum engine lifetime
- Ensures long oil drain intervals
- Optimum oxidation resistance
- Excellent environment protection because of low oil related emissions
- Backward compatible to older RENAULT specifications RN0700/ 0710

APPLICATION

LUKOIL GENESIS SPECIAL RN 5W-30 has been specially developed for:

- The latest RENAULT RN17 specification
- Use in gasoline and diesel engines

LUKOIL GENESIS SPECIAL RN 5W-30 can be mixed with other branded oils with the same specification level. But the full range of performance is only guaranteed if used pure.

For detailed information about your vehicle's lubrication and specifications, please refer to the manufacturer's user manual.

30. Jan. 2020, Page 1/2

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service technics.lubes@eu.lukoil.com.

TYPICAL TEST DATA

Property	Unit	Test method	LUKOIL GENESIS SPECIAL RN 5W-30
Density @ 15 °C	kg/m ³	DIN 51757	846
Flash point (COC)	°C	ISO 2592	≥220
Viscosity class	---	SAE J300	5W-30
Viscosity @ 40°C	mm ² /s	DIN 51562/T1	62,47
Viscosity @ 100°C	mm ² /s	DIN 51562/T1	12.1
Viscosity index	---	DIN ISO 2909	194
Pourpoint	°C	DIN ISO 3016	≤-39
Total Base Number (TBN)	mg KOH / g	ASTM D2896	7.5
Sulphated ash	% mass	DIN 51575	≤0.8

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

SHELF LIFE AND STORAGE

When stored in the original unopened containers in a dry place, this product has a shelf life of at least 60 months from the date of production.

SAFETY, HEALTH, ENVIRONMENT

This product doesn't contain any toxic ingredients. During storage, transportation and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed.

For further information on how to use LUKOIL products, please refer to the material safety data sheet:

<http://www.lukoil-lubricants.eu/>