

ROLF GT 5W-30 SN/CF motor oil

Synthetic

Description and uses:

High-grade easy flowing synthetic motor oil for gasoline and diesel engines including turbocharged engines. For all-season application.

High-quality base ingredients and cutting-edge additives provide a quick and easy engine start at low temperatures, excellent wear protection, and an extended oil change interval. Prevents deposit formation in the oil system, provides the engine cleanliness.

ROLF GT 5W-30 synthetic oil has the highest specification of motor oils for gasoline car engines – API SN.

Meets:

API SN/CF, ACEA C3-12, MB 229.51, BMW LL-04, GM DEXOS 2

Available package: 1 / 4 / 20 / 208 l

Typical Analysis:

Properties	Method	Value
SAE (J300)	5W-30	
Oil classification according to API	SN/CF	
Density at 15°C, g/cm ³	ASTM D 4025	0.853
Kinematic viscosity at 100°C, mm ² /s	ASTM D 445	12.1
Viscosity index	ASTM D 2270	170
Total Base Number (TBN), mg KOH/g	ASTM D 2896	6.5
Sulphated ash, %	ASTM D 874	0.8
Flash point, °C	ASTM D 92	235
Pour point, °C	ASTM D 97	minus 40



✓ Engine protection

✓ Fast cold start