



A brand of **TOTAL**

EVOLUTION 900 SXR 5W-40



Very high performance lubricant based upon ELF synthetics technology, designed for lubricating all Diesel car engines.

APPLICATIONS

All Diesel engines, especially those of recent technology

- Recommended for all supercharged or naturally aspirated Diesels in cars and light vans.

Even in very severe conditions

- Suitable for all types of service (urban, or on the highway or motorway) especially in very severe conditions.

Fast driving

- For all types of driving, especially at high speed.

All times of year, even the coldest weather

- Specially designed to meet the demands of the motor manufacturers as regards extended oil-change.

Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer

PERFORMANCES

International specifications

ACEA A3/B4
API: SN/CF

OEMs approvals

RENAULT
MERCEDES-BENZ

RN0710 et RN0700
MB-Approval 226.5

CUSTOMER BENEFITS

Best possible performance

- Excellent engine protection, particularly against wear in the timing system.

Excellent engine cleanliness and protection

- Ensures an exceptionally clean engine.

Easier starting in very cold conditions

- Outstanding thermal stability and oxidation resistance, guaranteeing that the oil will not degrade even in conditions of very severe use.

Longer engine life

- Immediate lubrication of engine components during cold starts, leading to longer engine life.

Extended oil-change intervals

- Lubricant performance sustained over time for extended oil change intervals.

CHARACTERISTICS

| | Method | Units | SAE Grade 5W-40 |
|--------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D1298 | kg/m ³ | 855 |
| Viscosity at 40°C | ASTM D445 | mm ² /s | 90 |
| Viscosity at 100°C | ASTM 445 | mm ² /s | 14,7 |
| Viscosity index | ASTM D2270 | - | 172 |
| Pour point | ASTM D97 | °C | - 42 |
| Flash point | ASTM D92 | °C | 230 |
| B.N. | ASTM D2896 | mgKOH/g | 10 |

The typical characteristics mentioned represent mean values