

Technical Data Sheet



Typical Inspection Data: Density @ 20°C 0.850 g/cm³ Viscosity @ 100°C 14.2 cSt Viscosity @ 40°C 87 cSt Viscosity Index 169 Viscosity CCS @ -30°C 6000 cP T.B.N. 8.0 mg KOH/g Sulphated Ash Mass 0.8% Zinc 0.10% Calcium 0.18% **Phosphorus** 0.08% Colour Brown Flash Point 230°C **Pour Point** -39°C

PD Plus 5W-40

Fully Synthetic

Official Approvals:

Approved under VW standard 505 00 and VW standard 505 01

Recommended by Comma for applications requiring:

FORD WSS M2C917-A; MB 229.31, MB 226.5; RN 0700, RN 0710; dexos 2; ACEA C3; API SN/CF

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW `Pumpe Düse' PD or unit injector engine. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 19.11.2021