

Quartz 9000 Energy HKS G-310 5W-30

Engine oil

KEY DATA



LIGHT VEHICLE RANGE

GASOLINE ENGINE OIL

SAE 5W-30

ADVANCED SYNTHETIC TECHNOLOGY

INTERNATIONAL STANDARDS

ACEA A5

API SL

MANUFACTURER APPROVALS ¹

Recommended by Kia Motors with
Factory Fill performance

¹ Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

Quartz 9000 Energy HKS G-310 is suitable for all petrol engines developed by Hyundai-Kia Motors Corporation. Quartz 9000 Energy HKS G-310 brings an outstanding protection against engine wear, ensures an optimal cleanliness and allows longer drain intervals.

Quartz 9000 Energy HKS G-310 can be used in the most difficult operating conditions (Motorways, dense city traffic).

Suitable for all driving style, especially sports driving and whatever the season.

CUSTOMERS BENEFITS

- 💧 Protection and cleanliness engine : Brings an outstanding protection against engine wear and ensure engine longevity.
- 💧 Long drain interval : Allows long drain intervals (30000km) thanks to an excellent resistance to oxidation.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	5W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	60.16
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	10.35
Density at 15°C	kg/m ³	ASTM D1298	854.9
Viscosity index	-	ASTM D2271	162
Pour point	°C	ASTM D97	-42
OC Flash point	°C	ASTM D93	234

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

