

EVOLUTION OW30

PRODUCT DESCRIPTION

KENNOL EVOLUTION 0W30 is a fully synthetic motor oil developed for petrol or diesel engines of passenger cars, including those equipped with direct injection, turbo-charged or not.

PROPERTIES

KENNOL EVOLUTION 0W30 is formulated from selected synthetic bases (ester + PAO) and top level performance additives to provide with special features, such as :

FEATURES	BENEFITS
High fluidity at low temperature	Extends engine life and allow to save fuel
Low volatility	Allows low oil consumption
Very high dispersing power	Enables your engine to be better cleaned and
	reduces exhaust fumes
Very high thermal stability	Guarantees good protection at high
	temperature

SPECIFICATIONS

KENNOL EVOLUTION 0W30 has been developed to meet the highest international standards, including :

SAE	0W30
ACEA	A3/B3/B4
API	SN/CF
VW	503.00/506.00/506.01
MB	229.3
BMW	LL-01
Viscosity @ 40°C (cSt)	62
Viscosity @ 100°C (cSt)	11,1
Viscosity Index	174
Viscosity CCS (cP)	4900 (@ -35°C)
Density @ 20°C	0,863
Viscosity HTHS (at 150 °C under high shear 10 ⁶ s-1) (cP)	3,6
Pour Point, °C	-45
Flash Point, °C	> 210
Volatility Noack 1H @ 250°C (%w)	12
TBN (mg KOH/g)	10,8

KENNOL EVOLUTION 0W30 has been mainly developed to answer the needs of specific engines featuring direct injection. Because this product was born on the track.

 $\label{lem:decomposition} \mbox{Direct download here: $http://www.kennol.com/FT/KENNOL_EVOLUTION_0W30_EN.pdf}$

All products may not be available locally. For more information, contact your distributor or visit www.kennol.com. Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.
© 2017 KENNOL. All rights reserved.