

ELITE EVOLUTION POWER 4 5W-30



AUTOMOTIVE

Lubricants

Description

ACEA C4 quality synthetic lubricant oil, specially recommended in vehicles with particle filters and exhaust fume treatment. Stands out for its low ash production (Low SAPS), and is the specific lubricant for Renault diesel vehicles that require RN0720 quality level. It is also a long-lasting lubricant, allowing significant extension of oil change intervals; always according to the manufacturer's recommendations,

Properties

- Its reduced ash content (Low SAPS) makes it essential for ensuring the durability of new technologies applied to reduce pollutant emission levels, such as diesel particle filters (DPF).
- The RN0720 quality level ensures high oil resistance to oxidation and a minimum formation of deposits in the piston, thus extending the oil change period.
- Contributes to reducing CO₂ emissions, obtaining fuel savings of up to 1 % compared to other lubricants under standard M111FE test conditions.

Quality Levels

- ACEA C4
- RENAULT RN0720

Technical specifications

| | UNIT | METHOD | VALUE |
|-----------------------|----------|-------------|-----------|
| SAE GRADE | | | 5W-30 |
| Density at 15 °C | g/mL | ASTM D 4052 | 0.854 |
| Viscosity at 100 °C | cSt | ASTM D 445 | 12.2 |
| Viscosity at 40 °C | cSt | ASTM D 445 | 70 |
| Viscosity at -30 °C | cP | ASTM D 5293 | 6600 max. |
| Viscosity index | - | ASTM D 2270 | 173 |
| Flash point, open cup | °C | ASTM D 92 | 200 min. |
| Pour point | °C | ASTM D 97 | -33 máx. |
| T.B.N. | mg KOH/g | ASTM D 2896 | 6.6 |

A safety data sheet is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3. September 2016.